

US010697865B2

(12) United States Patent

(54) PREPROCESSING APPARATUS FOR GAS ANALYSIS

(71) Applicant: Japan Agency for Marine-Earth
Science and Technology, Yokosuka-shi,

Kanagawa (JP)

(72) Inventor: Saburo Sakai, Yokosuka (JP)

(73) Assignee: JAPAN AGENCY FOR MARINE-EARTH SCIENCE AND TECHNOLOGY, Yokosuka-Shi (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 202 days.

(21) Appl. No.: 15/

15/757,184

(22) PCT Filed:

Sep. 6, 2016

(86) PCT No.:

PCT/JP2016/076107

§ 371 (c)(1),

(2) Date:

Mar. 2, 2018

(87) PCT Pub. No.: WO2017/043468 PCT Pub. Date: Mar. 16, 2017

(65) **Prior Publication Data**

US 2018/0252620 A1 Sep. 6, 2018

(30) Foreign Application Priority Data

Sep. 8, 2015 (JP) 2015-176635

(51) Int. Cl. G01N 1/00 (2006.01) G01N 1/22 (2006.01)

(Continued)

(Continued)

(10) Patent No.: US 10,697,865 B2

(45) Date of Patent:

Jun. 30, 2020

(58) Field of Classification Search

CPC G01N 1/22; G01N 30/12; G01N 30/20; G01N 31/00

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

FOREIGN PATENT DOCUMENTS

EP 2316020 5/2011 JP 2001-318007 A 11/2001 (Continued)

OTHER PUBLICATIONS

European Search Report dated May 7, 2019, 9 pages. (Continued)

Primary Examiner — Jamel E Williams
(74) Attorney, Agent, or Firm — Rankin, Hill & Clark
LLP

(57) ABSTRACT

Provided herein is a preprocessing apparatus for gas analysis that enables preprocessing for gas analysis to be performed without requiring a cryogen. A preprocessing apparatus for gas analysis 101 mainly includes a gas flow path 103, a cooling portion 105, and a plurality of valves V101 to V105 that serve as gas flow path connection changing means for changing the gas flow path. The cooling portion 105 is operable to cool the collecting portion 113, and is constituted from a heat conductor 121, a cooling device 127, and a sealed structure 129. The cooling device 127 can cooled a contact cooling section 131 to an extremely low temperature by utilizing electrical energy. The cooling device 127 is used to bring the collecting portion 113 to a first temperature at which the target gas to be analyzed is solidified, and to thereafter bring the collecting portion 113 to a second (Continued)

101 109 117 VACUUM PUMP PHOSPHORIC PRESSURE GAUGE ACTD 101 111 V103 V102 V105 V104 STIRLING 113 103 105 115 107 127

(56)

temperature at which only the target gas to be analyzed is gasified. By performing such processes, the target gas to be analyzed can be extracted by removing gases of impurities from a mixed gas.

19 Claims, 10 Drawing Sheets

(51)	Int. Cl.	
	G01N 31/00	(2006.01)
	G01N 30/12	(2006.01)
	G01N 30/20	(2006.01)
	G01N 33/00	(2006.01)
	G01N 30/02	(2006.01)

(52) U.S. Cl. CPC G01N 30/20 (2013.01); G01N 31/00 (2013.01); G01N 33/0047 (2013.01); G01N 2030/025 (2013.01); G01N 2030/121 (2013.01)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2002-340755	A		11/2002	
JP	2003-066019	A		3/2003	
JP	2004-212075	A		7/2004	
JP	2014-529080	A		10/2014	
WO	WO-2010004404	A1	*	1/2010	G01N 30/12

OTHER PUBLICATIONS

Barron, "Cryogenic Heat Transfer" Dec. 31, 1999, CRC Press, XP002790845, pp. 52-54. Matsuhisa, "Oxygen and Hydrogen Isotope Geology (1)", Geologi-

cal News, Feb. 1978 Issue, No. 282, 9 pages.

Isoprime, "Carbonate Analysis on the MultiCarb Dual-Inlet System", (http://www.isoprime.co.uk/files/TN010.pdf), 1 page.

Kasama, et al., "Analysis of Minute Amount of Volatile Component by P&T-GC/MS Method", Nichias Technical Report, No. 328, June Issue, 2001, 7 pages.

^{*} cited by examiner