

The Development of Design Methodology for High-performance Turbomachinery Blades and Components using Large-scale Aerodynamic and Structural Interaction Analysis

Project Representative

Sakae Kawasaki

Toshiba Corporation

Authors

Sakae Kawasaki^{*1}, Naoki Shibukawa^{*2}, Yoshiki Niizeki^{*2}, Daisuke Nomura^{*2}, Tadashi Tanuma^{*3}, Yasuhiro Sasao^{*4}, Satoru Yamamoto^{*5}, Hiroshi Okuda^{*6}, Gaku Hashimoto^{*6}, Satoru Watanabe^{*7}, Takao Kobayashi^{*7}, Keiji Suehiro^{*8}, Xi Yuen^{*8}, Yoshinari Fukui^{*9}, Yuichi Hirokawa^{*9}, Noriaki Nishikawa^{*9}

* 1 Keihin Product Operations, Toshiba Corporation

* 2 Power and Industrial Systems Research and Development Center, Toshiba Corporation

* 3 Applied Fluid Dynamics & Energy Machinery Systems, Joint Program Center, Teikyo University

* 4 Graduate School of Science & Engineering, Teikyo University

* 5 Dept. of Computer and Mathematical Sciences, Tohoku University

* 6 Graduate School of Frontier Sciences, The University of Tokyo

* 7 Toshiba Information Systems Corporation

* 8 Advanced Soft Corporation

* 9 Japan Agency for Marine-Earth Science and Technology

Abstract

Power generation systems that employ steam turbines produce more than 60% of the global supply of electricity, and the global electricity generation is projected to increase by a factor of about 1.7 by 2035. Consequently, the development and practical realization of technologies required to enhance the efficiency of steam turbines for power generation should be encouraged to meet the electricity demand while limiting and reducing global greenhouse gas emissions.

The aim of this project is to increase steam turbine efficiency with the development of high-performance blade and exhaust hood design methodology using large-scale aerodynamic and structural interaction analysis.

Main components of steam turbines are turbine stages that consist with stator blades and rotating blades. Aerodynamic optimum designs of stator blades are already introduced in many designs of actual operating commercial steam turbine units. However, aerodynamic optimum designs of rotating blades are still difficult due to high centrifugal force and vibration stress on rotating blades. The current

project focuses on rotating blades and exhaust diffusers that affect the flow field just downstream of last stage long blades.

The large-scale high-accuracy CFD analysis of unsteady wet steam flows has been successfully introduced for simulations of low pressure exhaust diffuser using the Earth Simulator of Japan Agency for Marine-Earth Science and Technology. This result shows that the diffuser domain analysis can provide static pressure recovery coefficients and its circumferential deviations with enough accuracy for design use except correct location predictions of separations.

The unsteady flow analyses of the typical designed last stage with the measured downstream static pressure distribution as the outlet boundary condition were conducted using a package software. The inlet static pressure circumferential distribution of the present exhaust diffuser caused negligible effect on the last stage efficiency.

The large-scale parallel computing Finite Element Analysis of turbine blades with inter-connection parts has been also successfully introduced on the Earth Simulator. The calculation result shows that the eigen frequencies of the present group of loosely-connected six rotating blades correspond well to the existing measured data. For the next step, the unsteady structural analysis is being conducted with the calculated unsteady forces on the rotating blades as the FEA boundary conditions.

Keywords: aerodynamic and structural interaction analysis, steam turbine, efficiency, blade, unsteady aerodynamic force