

geoVISION - sonicVISION - APWD
 Gamma Ray - Resistivity - Image - Compressional - APWD
 12.25in Recorded Mode Log. True Vertical Depth
 Sub Sea 1:200



Company: JAMSTEC

Well: C0012H

Field: Nankai Trough - Kumano Basin

Rig Name: Chikyū

Prefecture: Wakayama

Country: Japan

Latitude: 32° 44' 52.698" N

Custom:

12JAP0016

Longitude: 136° 55' 2.106" E

Rig Name:

Chikyū

Block:

Rig Type:

Drill Vessel

FL: Philippine Sea

FL1: X = 679 623.175 m

FL2: Y = 3 624 973.513 m

Log Measured From: - Drill Floor: 28.50 m
 Permanent Datum: - Mean Sea Level



Ground Level: 3509.50 m

Acquisition Dates: 04-Dec-2012 -- 06-Dec-2012

Other Services:

Log Interval: 3525.00(m) -- 4247.73(m)

DWOB, DTOR

Index Types: SSTVD

Direction and Inclination

Index Scales: 1:200


Drilling Mechanics

Depth Source: Driller's Depth

Depth Sensor: DES

Print Type: Final

Spud Date: 03-Dec-2012



Disclaimer

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

Contents


1. Header
2. Disclaimer
3. Contents
4. Well Sketch
5. Borehole Size/Casing/Tubing Record
6. Operational Run Summary
7. Borehole Fluids
8. Remarks and Equipment Summary
9. Survey Record
10. UDComposite1
 - 10.1 Integration Summary
 - 10.2 Composite Summary
 - 10.3 Log (Sonic-GVR Image-APWD Depth RM No Tick)
 - 10.4 Parameter Listing
11. 002
 - 11.1 Integration Summary

- 11.2 Composite Summary
- 11.3 Log (DML Depth RM)
- 11.4 Parameter Listing
- 12. Calibration Report
- 13. Tail

Well Sketch

Driller Depth

3538.00 m



4248.00 m

Open Hole 12.25in

Borehole Size/Casing Record

| | | | | | |
|----------------------|-------|--|--|--|--|
| Bit | | | | | |
| Bit Size (in) | 12.25 | | | | |
| Top Driller (m) | 3538 | | | | |
| Bottom Driller (m) | 4248 | | | | |

Operational Run Summary

| | | | | | |
|----------------------------------|-----------------------------|--|--|--|--|
| Parameter (unit) | 002 | | | | |
| Date Log Started | 04-Dec-2012 | | | | |
| Time Log Started | 07:17:28 | | | | |
| Date Log Finished | 06-Dec-2012 | | | | |
| Time Log Finished | 20:37:57 | | | | |
| Bit Size (in) | 12.250 | | | | |
| Bit Start Depth (m) | 3538.00 | | | | |
| Bit Stop Depth (m) | 4248.00 | | | | |
| Top Log Interval (m) | 3538.00 | | | | |
| Bottom Log Interval (m) | 4247.74 | | | | |
| Max Hole Deviation (deg) | 2.63 | | | | |
| Azimuth of Max Deviation (deg) | 328.45 | | | | |
| Logging Unit Number | OLU-KC-504 | | | | |
| Logging Unit Location | Comp Deck | | | | |
| Recorded By | Wang Feng Shao Kai | | | | |
| Witnessed By | Yoshi Sanada Yukari Kido | | | | |
| Service Order Number | 12JAP0016 | | | | |


Borehole Fluids

| | | | | | |
|------------------------------------|-------------|--|--|--|--|
| Parameter(unit) | 002 | | | | |
| Fluid Type | Water | | | | |
| Fluid Name | Sea Water | | | | |
| Max Recorded Temperatures (degC) | 10 | | | | |
| Source of Sample | Active Tank | | | | |
| Salinity (ppm) | 30470.42 | | | | |
| Density (g/cm3) | 1.04 | | | | |

| | | | | | | |
|--------------------------------|-------------|--|--|--|--|--|
| Funnel Viscosity (s) | | | | | | |
| Fluid Loss (cm3) | | | | | | |
| PH | 11.6 | | | | | |
| Source RMF | | | | | | |
| RMC | Pressed | | | | | |
| RM @ Meas Temp (ohm.m@degC) | 0.22 @ 20.3 | | | | | |
| RMF @ Meas Temp (ohm.m@degC) | 0.15 @ 20 | | | | | |
| RMC @ Meas Temp (ohm.m@degC) | | | | | | |
| RM @ BHT (ohm.m@degC) | 0.3 @ 10 | | | | | |
| RMF @ BHT (ohm.m@degC) | 0.2 @ 10 | | | | | |
| RMC @ BHT (ohm.m@degC) | NaN @ 10 | | | | | |
| Total Solid (%) | | | | | | |
| High Gravity Solids (%) | | | | | | |

Remarks and Equipment Summary

| 002: Toolstring | | | | 002: Remarks | |
|---|-------------------------------|-------------------------------|---------------|--|--|
| Equip name Stab: 8 1/4":7671 8 | Length 29.08 | MP name Schumberger | Offset | Data presented is Recorded Mode data which was acquired while drilling. | |
| | | | | Depth reference is driller's depth measured from Rotary Table. | |
| | | | | geoVISION record rate is 10s, sonicVISION record rate is 10s, APWD record rate is 10s. | |
| | | | | geoVISION GR is corrected for bit size, tool size and mud weight. No potassium concentration in mud. | |
| | | | | geoVISION resistivity is environmentally corrected for bit size and mud resistivity. | |
| | | | | sonicVISION compressional slowness is processed by DCS. | |
| | | | | Reason for POOH: Well TD. | |
| | | | | Drilling Time: 25.18 hrs | |
| | | | | Pumping Time: 36.30 hrs | |
| | | | | Warning in calibration list is due to MaxWell bug. | |
| | | | | | |
| SONICVISION8:E 6207 | 26.7 | Schlumberger | | | |
| TELE825-IWOB:G 0159 | 18.51 | Schlumberger | | | |



ARC8:2791-SRPC 10.08

RAB8:42825/413 47
4.17

Bit: 12 1/4":A162 762
0.3

Lengths are in m
Maximum Outer Diameter = 12.250 in
Line: Sensor Location, Value: Gating Offset
All measurements are relative to TOOL_ZERO

Survey Record

Survey Calculation

| | | | |
|--------------------|-----------------------------|----------------------------|---------------------------------|
| Method : | Minimum Radius of Curvature | DLS Method : | Lubinski |
| North Reference : | Grid North | Total Correction Formula : | Magnetic Dec - Grid Convergence |
| Grid Convergence : | 1.03 deg | | |

Dig Location

Rig Location
 Latitude : 32° 44' 52.698" N Longitude : 136° 55' 2.106" E
Tie In Point
 Measured Depth: 0.00 m Inclination: 0.00 deg Azimuth: 0.00 deg
 True Vertical Depth: 0.00 m North Displacement: 0.00 m East Displacement: 0.00 m
 N/-S VSec Origin: 0.00 m E/-W VSec Origin: 0.00 m Vertical Section Azimuth: 0.00 deg

D&I Inits Computed and Values Used - 002
 Geomagnetic Model : BGGM 2011 Geomagnetic Date : 04-Dec-2012
 Computed Location B : 45580.54 nT +/- 300.00nT Used Location B : 45580.54 nT +/- 300.00nT
 Computed Location G : 9.80 m/s2 +/- 0.02m/s2 Used Location G : 9.80 m/s2 +/- 0.02m/s2
 Computed Magnetic Dip : 46.04 deg +/- 0.45deg Used Magnetic Dip : 46.04 deg +/- 0.45deg
 Computed Magnetic Dec : -6.53 deg Used Magnetic Dec : -6.53 deg
 Computed Total Correction : -7.56 deg Used Total Correction : -7.56 deg

Survey Quality Index
 2 : Long Survey failed mag criteria 4 : Long Survey failed all criteria 9 : Manual
 28 : Tie-In Point

Survey Correction Index
 0 : No correction

Survey Description Index
 0 : Not Flagged Survey

| Seq | MD (m) | Incl (deg) | Azim (deg) | Course (m) | TVD (m) | V Sec (m) | N/ -S (m) | E/ -W (m) | Closure (m) | at Azim (deg) | DLS deg/30m | Tool Type | QI | CI | DI |
|-----|---------|------------|------------|------------|---------|-----------|-----------|-----------|-------------|---------------|-------------|-----------|----|----|----|
| 1 | 0.00 | 0.00 | 0.00 | ---- | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 90.00 | 0.00 | TIP | 28 | 0 | 0 |
| 2 | 3538.00 | 0.00 | 0.00 | 3538.00 | 3538.00 | 0.00 | 0.00 | 0.00 | 0.00 | 90.00 | 0.00 | Other | 9 | 0 | 0 |
| 3 | 3655.73 | 1.75 | 349.87 | 117.73 | 3655.71 | 1.77 | 1.77 | -0.32 | 1.79 | 349.87 | 0.45 | TeleScope | 2 | 0 | 0 |
| 4 | 3693.83 | 1.51 | 351.80 | 38.09 | 3693.79 | 2.83 | 2.83 | -0.49 | 2.88 | 350.21 | 0.19 | TeleScope | 4 | 0 | 0 |
| 5 | 3732.14 | 1.40 | 344.53 | 38.32 | 3732.10 | 3.78 | 3.78 | -0.69 | 3.85 | 349.72 | 0.17 | TeleScope | 2 | 0 | 0 |
| 6 | 3770.57 | 1.23 | 341.43 | 38.43 | 3770.51 | 4.63 | 4.63 | -0.94 | 4.72 | 348.49 | 0.15 | TeleScope | 2 | 0 | 0 |
| 7 | 3808.99 | 1.20 | 347.84 | 38.42 | 3808.93 | 5.41 | 5.41 | -1.16 | 5.53 | 347.92 | 0.11 | TeleScope | 4 | 0 | 0 |
| 8 | 3847.15 | 1.24 | 342.38 | 38.16 | 3847.08 | 6.19 | 6.19 | -1.37 | 6.34 | 347.56 | 0.10 | TeleScope | 4 | 0 | 0 |
| 9 | 3885.57 | 1.29 | 340.44 | 38.42 | 3885.49 | 7.00 | 7.00 | -1.64 | 7.18 | 346.83 | 0.05 | TeleScope | 4 | 0 | 0 |
| 10 | 3923.41 | 1.32 | 334.69 | 37.84 | 3923.32 | 7.79 | 7.79 | -1.97 | 8.04 | 345.84 | 0.11 | TeleScope | 2 | 0 | 0 |
| 11 | 3961.64 | 1.39 | 331.68 | 38.23 | 3961.54 | 8.60 | 8.60 | -2.38 | 8.92 | 344.56 | 0.08 | TeleScope | 2 | 0 | 0 |
| 12 | 3999.88 | 1.32 | 329.17 | 38.24 | 3999.77 | 9.39 | 9.39 | -2.82 | 9.80 | 343.27 | 0.07 | TeleScope | 4 | 0 | 0 |
| 13 | 4037.88 | 1.38 | 326.23 | 38.00 | 4037.75 | 10.14 | 10.14 | -3.30 | 10.67 | 341.97 | 0.07 | TeleScope | 4 | 0 | 0 |
| 14 | 4075.87 | 1.52 | 331.96 | 38.00 | 4075.74 | 10.97 | 10.97 | -3.79 | 11.61 | 340.93 | 0.16 | TeleScope | 2 | 0 | 0 |
| 15 | 4113.78 | 1.89 | 321.90 | 37.91 | 4113.63 | 11.91 | 11.91 | -4.42 | 12.70 | 339.65 | 0.38 | TeleScope | 2 | 0 | 0 |
| 16 | 4152.27 | 2.08 | 326.15 | 38.49 | 4152.10 | 12.99 | 12.99 | -5.20 | 13.99 | 338.19 | 0.18 | TeleScope | 4 | 0 | 0 |
| 17 | 4190.73 | 2.46 | 326.26 | 38.46 | 4190.53 | 14.25 | 14.25 | -6.04 | 15.48 | 337.02 | 0.30 | TeleScope | 2 | 0 | 0 |
| 18 | 4231.12 | 2.63 | 328.45 | 40.39 | 4230.87 | 15.77 | 15.77 | -7.01 | 17.26 | 336.02 | 0.14 | TeleScope | 2 | 0 | 0 |

UDComposite 1

Integration Summary

| Output Channel(s) | Output Description | Input Parameter | Output Value | Unit |
|-------------------|--------------------|-----------------|--------------|------|
|-------------------|--------------------|-----------------|--------------|------|

Composite Summary

| Run Name | Pass Objective | Direction | Top | Bottom | Start | Stop | Include Parallel Data |
|----------|----------------|-----------|-----------|-----------|------------------------|------------------------|-----------------------|
| 002 | Drilling | Down | 3529.43 m | 4248.00 m | 04-Dec-2012 7:17:28 AM | 06-Dec-2012 8:37:57 PM | |

All depths are referenced to toolstring zero





Log **UDComposite 1**




Description: GVR Resistivity, Deep Button Image Format: Log (Sonic-GVR Image-APWD Depth RM No Tick) Index Scale: 1:200 Index Unit: m Index Type: SSTVD Creation Date: 08-Dec-2012 12:11:48

| | | |
|--|-------|-----|
| Ring Resistivity Time After Bit (TAB_RES_RING) RAB[1] | | |
| 0 | h | 3 |
| Gamma Ray (GR) RAB[1] RM | | |
| 0 | gAPI | 150 |
| Rate of penetration averaged over the last 5 ft (1.5 m) (ROP5) RT | | |
| 100 | m/h | 0 |
| Delta-T Compressional (DTCO) sonicVISION[1] RM | | |
| 140 | us/ft | 40 |

| |
|--|
| Rotational Speed (RPM) RAB[1] RM |
| 0 c/min 200 |


| | | | |
|---|-----|-------|-----|
| Bit Resistivity (RES_BIT) RAB[1] RM | 0.2 | ohm.m | 200 |
| Ring Resistivity (RES_RING) RAB[1] RM | 0.2 | ohm.m | 200 |
| Deep Button Resistivity (RES_BD) RAB[1] RM | 0.2 | ohm.m | 200 |
| Medium Button Resistivity (RES_BM) RAB[1] RM | 0.2 | ohm.m | 200 |
| Shallow Button Resistivity (RES_BS) RAB[1] RM | 0.2 | ohm.m | 200 |












RES_BS
 RES_BM
 RES_BD
 RES_RING


DTCO
 ROP5
 ROP






































| | | | |
|---|-----|-------|-----|
| Ring Resistivity Time After Bit (TAB_RES_RING) RAB[1] RM | 0 | h | 3 |
| Gamma Ray (GR) RAB[1] RM | 0 | gAPI | 150 |
| Rate of penetration averaged over the last 5 ft (1.5 m) (ROP5) RT | 100 | m/h | 0 |
| Delta-T Compressional (DTCO) sonicVISION[1] RM | 140 | us/ft | 40 |

| | | | |
|----------------------------------|---|-------|-----|
| Rotational Speed (RPM) RAB[1] RM | 0 | c/min | 200 |
|----------------------------------|---|-------|-----|



| | | | |
|---|-----|-------|-----|
| Bit Resistivity (RES_BIT) RAB[1] RM | 0.2 | ohm.m | 200 |
| Ring Resistivity (RES_RING) RAB[1] RM | 0.2 | ohm.m | 200 |
| Deep Button Resistivity (RES_BD) RAB[1] RM | 0.2 | ohm.m | 200 |
| Medium Button Resistivity (RES_BM) RAB[1] RM | 0.2 | ohm.m | 200 |
| Shallow Button Resistivity (RES_BS) RAB[1] RM | 0.2 | ohm.m | 200 |

Description: GVR Resistivity, Deep Button Image Format: Log (Sonic-GVR Image-APWD Depth RM No Tick) Index Scale: 1:200 Index Unit: m Index Type: SSTVD Creation Date: 08-Dec-2012 12:11:48

Channel Processing Parameters

002: Parameters

| Parameter | Description | Tool | Value | Unit |
|---------------|---|--------------|-------------------|---------|
| BHK | Drilling Fluid Potassium Concentration | Borehole | 0 | % |
| BHT | Bottom Hole Temperature | Borehole | 10 | degC |
| BS | Bit Size | DNMSESSION | 12.25 | in |
| CDTS | Correction for Delta-T Shale, Empirical | Borehole | 100 | us/ft |
| COLL | Label Slowness Lower Limit - Monopole P&S Compressional | SONICVISION8 | 65 | us/ft |
| COUL | Label Slowness Upper Limit - Monopole P&S Compressional | SONICVISION8 | 110 | us/ft |
| DDEL | Digitizing Delay | SONICVISION8 | 300 | us |
| DEPTH_SEL | Depth Selection Parameter | DNMSESSION | Driller's Depth | |
| DFD | Drilling Fluid Density | Borehole | 1.04 | g/cm3 |
| DFT | Drilling Fluid Type | Borehole | Water | |
| DTF | Delta-T Fluid | Borehole | 189 | us/ft |
| DTM | Delta-T Matrix | Borehole | 56 | us/ft |
| FIN_DTSH_MODE | Final DT Compressional STC Processing Mode | SONICVISION8 | DDBHC | |
| FIN_DTSH_SRC | Final DT Compressional Source | SONICVISION8 | Reassigned Uphole | |
| FIN_DTSH_MODE | Final DT Shear Slowness STC Processing Mode | SONICVISION8 | DDBHC | |
| GGRD | Geothermal Gradient | Borehole | 18.23 | degC/km |
| GRSE_RM | Generalized Mud Resistivity Selection for Recorded Mode | Borehole | REMS | |
| GTSE_RT | Generalized Temperature Selection for Realtime Mode | Borehole | GTEM_LINEST(RT) | |
| ITT_OFFSET | Integrated Transit Time Offset | SONICVISION8 | 0 | ms |
| MST | Mud Sample Temperature | Borehole | 20.3 | degC |
| NWED | Noise Window End | SONICVISION8 | 2200 | us |

| | | | | |
|----------------|---|--------------|--------------------|-------|
| NWST | Noise Window Start | SONICVISION8 | 600 | us |
| RES_BD_IMG_SEL | GVR Output Resistivity Image Selection, Deep Button | RAB8 | Compensated Uphole | |
| RMS | Resistivity of Mud Sample | Borehole | 0.22 | ohm.m |
| SBIN | Search Band Inset | SONICVISION8 | 200 | |
| SBWD | Search Band Width | SONICVISION8 | 1600 | |
| SHLL | Label Slowness Lower Limit - Monopole P&S Shear | SONICVISION8 | 75 | us/ft |
| SHT | Surface Hole Temperature | Borehole | 2 | degC |
| SHUL | Label Slowness Upper Limit - Monopole P&S Shear | SONICVISION8 | 240 | us/ft |
| SIGE | Waveform Signal End Time | SONICVISION8 | 2000 | us |
| SIGM | Waveform Signal Move Out | SONICVISION8 | 130 | us/ft |
| SIGST | Waveform Signal Start Time | SONICVISION8 | 1500 | us |
| SPFS | Sonic Porosity Formula | Borehole | Raymer-Hunt | |
| SPSO_LWD | Sonic Porosity Source Logging While Drilling | SONICVISION8 | DTRA | |
| SWD_FIL_HIGH | Pre-STC filter high frequency cutoff (in kHz) | SONICVISION8 | 0 | kHz |
| SWD_FIL_LENG | Pre-STC filter length | SONICVISION8 | 1 | |
| SWD_FIL_LOW | Pre-STC filter low frequency cutoff (in kHz) | SONICVISION8 | 0 | kHz |
| SWD_FILTER | Pre-STC Filter Selection | SONICVISION8 | No Filter | |
| SWD_PR_SEL | Sonic Processing Option | SONICVISION8 | Both | |
| TD | Total Measured Depth | Borehole | 4248 | m |
| TEMP_SEL_RAB | RAB Temperature Selection | RAB8 | Tool | |

Tool Control Parameters

002: Parameters

| Parameter | Description | Tool | Value | Unit |
|-----------|--|------------|-------|------|
| OFFBTM_TH | Threshold for deciding whether the bit is off bottom | DNMSESSION | 0.6 | m |

002

Integration Summary

| Output Channel(s) | Output Description | Input Parameter | Output Value | Unit |
|-------------------|--------------------|-----------------|--------------|------|
|-------------------|--------------------|-----------------|--------------|------|

Pass Summary

| Run Name | Pass Objective | Direction | Top | Bottom | Start | Stop | Include Parallel Data |
|----------|----------------|-----------|-----------|-----------|------------------------|------------------------|-----------------------|
| 002 | Drilling | Down | 3529.43 m | 4248.00 m | 04-Dec-2012 7:17:28 AM | 06-Dec-2012 8:37:57 PM | |



All depths are referenced to toolstring zero



Log


002: Drilling



Description: Format: Log (DML Depth RM) Index Scale: 1:200 Index Unit: m Index Type: SSTVD Creation Date: 08-Dec-2012 12:12:19



| | | | | |
|---|--|---|---------|-------|
| Collar Rotational Speed (CRPM) TELE825-IW OB RT | Downhole Annulus Pressure (DHAP) ARC8 RM | 0 | kPa | 60000 |
| | Downhole Torque (MWD) (DTOR) TELE825-IWOB RT | 0 | kN.m | 20 |
| Rate of penetration averaged over the last 5 ft (1.5 m) (ROP5) RT | Downhole Annulus Temperature (DHAT) ARC8 RM | 0 | degC | 20 |
| | Downhole Weight on Bit (DWOB) TELE825-IWOB RT | 0 | kN | 200 |
| Standpipe Pressure (SPPA) RT | Equivalent Circulating Density (ECD) ARC8 RM | 1 | g/cm3 | 1.2 |
| | Surface Weight On Bit (SWOB) RT | 0 | kN | 200 |
| Total flow rate of all active pumps (TFLO) RT | Equivalent Static Density (ESD) ARC8 RT | 1 | g/cm3 | 1.2 |
| | | 0 | gal/min | 1500 |






































Rate of penetration averaged over the last 5 ft (1.5 m) (ROP5) RT

Collar Rotational

Downhole Annulus Pressure (DHAP) ARC8 RM

Downhole Torque (MWD) (DTOR) TELE825-IWOB RT

| | | | | | | | | | |
|---|---------|-------|---|--|-------|-------|---|------|-----|
| 100 | m/h | 0 | Speed (CRPM) | 0 | kPa | 60000 | 0 | kN.m | 20 |
| Standpipe Pressure (SPPA) RT | | | TELE825-IW OB RT | Downhole Annulus Temperature (DHAT) ARC8 RM | | | Downhole Weight on Bit (DWOB) TELE825-IWOB RT | | |
| 0 | kPa | 35000 | 0 | c/min | 400 | 0 | degC | 20 | 0 |
| Total flow rate of all active pumps (TFLO) RT | | | Stick Slip Indicator (STICK) TELE825-IW OB RT | Equivalent Circulating Density (ECD) ARC8 RM | | | 0 | | |
| 500 | gal/min | 1500 | | 1 | g/cm3 | 1.2 | Surface Weight On Bit (SWOB) RT | | |
| | | | 0 | c/min | 400 | 1 | g/cm3 | 1.2 | 0 |
| | | | Equivalent Static Density (ESD) ARC8 RT | | | 0 | | | 200 |
| | | | | | | kN | | | 200 |
| | | | | | | kN | | | 200 |

Description: Format: Log (DML Depth RM) Index Scale: 1:200 Index Unit: m Index Type: SSTVD Creation Date: 08-Dec-2012 12:12:19

Calibration Report

RAB8 (GeoVision Resistivity 825) Calibration - Run 002

Primary Equipment :

Electronics Chassis RBEC 865

M21V - Resistivity

Master (Time Frame File): 04:11:41 23-Nov-2012

| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | | | | | | | | | |
|---|------|--------|---------|-----------|---------|------------|---|--|--|--|--|--|--|--|--|
| Monitor 2 at T1 Calibration Coefficient | | Master | 1.00000 | 0.90000 | 1.02224 | 1.20000 | <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> </table> | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

M22V - Resistivity

Master (Time Frame File): 04:11:41 23-Nov-2012

| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | | | | | | | | | |
|---|------|--------|---------|-----------|---------|------------|---|--|--|--|--|--|--|--|--|
| Monitor 2 at T2 Calibration Coefficient | | Master | 1.00000 | 0.90000 | 0.99342 | 1.20000 | <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> </table> | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

M01V - Resistivity

Master (Time Frame File): 04:11:41 23-Nov-2012

| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | | | | | | | | | |
|---|------|--------|---------|-----------|---------|------------|---|--|--|--|--|--|--|--|--|
| Monitor 0 at T1 Calibration Coefficient | | Master | 1.00000 | 0.90000 | 1.05380 | 1.20000 | <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> </table> | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

M02V - Resistivity

Master (Time Frame File): 04:11:41 23-Nov-2012

| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | | | | | | | | | |
|---|------|--------|---------|-----------|---------|------------|---|--|--|--|--|--|--|--|--|
| Monitor 0 at T2 Calibration Coefficient | | Master | 1.00000 | 0.90000 | 1.04467 | 1.20000 | <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> </table> | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

R1V - Resistivity

Master (Time Frame File): 04:11:41 23-Nov-2012

| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | | | | | | | | | |
|------------------------------------|------|--------|---------|-----------|---------|------------|---|--|--|--|--|--|--|--|--|
| Ring at T1 Calibration Coefficient | | Master | 0.01000 | 0.00950 | 0.01096 | 0.01250 | <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> </table> | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

R2V - Resistivity

Master (Time Frame File): 04:11:41 23-Nov-2012

| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | | | | | | | | | |
|------------------------------------|------|--------|---------|-----------|---------|------------|---|--|--|--|--|--|--|--|--|
| Ring at T2 Calibration Coefficient | | Master | 0.01000 | 0.00950 | 0.01097 | 0.01250 | <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> </table> | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

BDM1 - Resistivity

Master (Time Frame File): 04:11:41 23-Nov-2012

| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | | | | | | | | | |
|---|------|--------|---------|-----------|---------|------------|---|--|--|--|--|--|--|--|--|
| Button Deep at T1 Calibration Coefficient | | Master | 0.00067 | 0.00057 | 0.00066 | 0.00077 | <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> </table> | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

BDM2 - Resistivity

Master (Time Frame File): 04:11:41 23-Nov-2012

| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | | | | | | | | | |
|---|------|--------|---------|-----------|---------|------------|---|--|--|--|--|--|--|--|--|
| Button Deep at T2 Calibration Coefficient | | Master | 0.00067 | 0.00057 | 0.00066 | 0.00077 | <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> </table> | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

BMM1 - Resistivity

Master (Time Frame File): 04:11:41 23-Nov-2012

| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | | | | | | | | | |
|---|------|--------|---------|-----------|---------|------------|---|--|--|--|--|--|--|--|--|
| Button Medium at T1 Calibration Coefficient | | Master | 0.00067 | 0.00057 | 0.00069 | 0.00077 | <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> </table> | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

BMM2 - Resistivity

Master (Time Frame File): 04:11:41 23-Nov-2012

| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | | | | | | | | | |
|---|------|--------|---------|-----------|---------|------------|---|--|--|--|--|--|--|--|--|
| Button Medium at T2 Calibration Coefficient | | Master | 0.00067 | 0.00057 | 0.00069 | 0.00077 | <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> <tr><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td><td style="width: 20px; height: 15px;"></td></tr> </table> | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

| BSM1 - Resistivity | | | | | | | |
|--|------|----------------------|---------|-----------|---------|------------|--|
| Master (Time Frame File): | | 04:11:41 23-Nov-2012 | | | | | |
| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | |
| ⚠ Button Shallow at T1 Calibration Coefficient | | Master | 0.00067 | 0.00057 | 0.00067 | 0.00077 | |
| BSM2 - Resistivity | | | | | | | |
| Master (Time Frame File): | | 04:11:41 23-Nov-2012 | | | | | |
| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | |
| ⚠ Button Shallow at T2 Calibration Coefficient | | Master | 0.00067 | 0.00057 | 0.00067 | 0.00077 | |
| PGR - Gamma Ray: Blanket | | | | | | | |
| Master (Time Frame File): | | 02:46:22 23-Nov-2012 | | | | | |
| Measurement | Unit | Phase | Nominal | Low Limit | Actual | High Limit | |
| ⚠ Gamma Ray API Conversion Factor | | Master | 8.5500 | 6.5000 | 10.2700 | 10.6000 | |

Company: JAMSTEC
Well: C0012H
Field: Nankai Trough - Kumano Basin
Rig Name: Chikyu
Prefecture: Wakayama
Country: Japan



geoVISION - sonicVISION - APWD
 Gamma Ray - Resistivity - Image - Compressional - APWD
 12.25in Recorded Mode Log. True Vertical Depth Sub Sea 1:200

