

Data Format of Levels 3 - 4 for Radiosonde data obtained during the YMC

November 23, 2021

<< Basic Information >>

Radiosonde type : Vaisala RS41-SG
Processor : MW41
Original data archive : ASCII files are archived every 1 second (~ Aug. 20, 2018)
or 2 seconds (Aug. 21, 2018 ~).

<< Processing Level >>

Level-0 Original
Level-1 Same as original except for their format
Level-2 Only apparent error data have been removed.
Level-3 Additional corrections have been made.
Level-4 Same as Level-3 except for their format (5 hPa interval from 1000 hPa to 80 hPa in addition to the surface value, etc.).

<< Data Format >>

Level-3

| | | |
|--------|------------|---|
| Header | Line-01 | Project ID |
| | Line-02 | Launch site/ID |
| | Line-03 | Location in deg-E, deg-N, height in meter |
| | Line-04 | Actual Launch Time in UTC |
| | Line-05 | Nominal Launch Time in UTC |
| | Line-06 | Serial Number / Radiosonde Type |
| | Line-07 | Ground station software |
| | Line-08-11 | Remarks |

Data

Following parameters are archived every 1 second as (f7.1, 2f8.2, 2x, 7f7.1, f8.0)

Time in second
Longitude in degree East
Latitude in degree North
Pressure in hPa
Temperature in degree C
Dewpoint temperature in degree C
Relative Humidity with respect to water in %
Zonal wind component in m/sec
Meridional wind component in m/sec
Mixing ratio in g/kg
Height in meters

Level-4

Data

Following parameters are stored every 5hPa from 1000hPa to 80hPa in addition to the surface as (2f8.2, 2x, 11f7.1, f8.0)

Longitude in degree East

Latitude in degree North

Pressure in hPa

Temperature in degree C

Dewpoint temperature in degree C

Relative Humidity with respect to water in %

Zonal wind component in m/sec

Meridional wind component in m/sec

Mixing ratio in g/kg

Specific Humidity ratio in g/kg

Potential temperature in K

Equivalent potential temperature in K

Saturated equivalent potential temperature in K

Height in meters

<< Remarks >>

Both Level-3 and 4 contain two directories expressed as *.0 and *.1, respectively. Their difference is that the latter adopted the method to correct near ground surface temperature and humidity values which might be affected by the surrounding structure based on Yoneyama et al. (2002), which was originally developed for ship-based observation. It is recommended to use “*.0” if researchers study actual local condition, while “*.1” may be adequate to see large-scale atmospheric condition. See the following reference for more details on the correction method.

- Reference -

Yoneyama, K., M. Hanyu, S. Sueyoshi, F. Yoshiura, and M. Katsumata, 2002: Radiosonde observation from the ship in the tropical region. *JAMSTECR*, **45**, 31-39. https://www.jamstec.go.jp/dcop/e/publications/pdf/Yoneyama-et-al_2002_JAMSTECR.pdf

<< Acknowledgments >>

We'd like to express our sincere thanks to the **Meteorological Service Singapore** for their kind offer of their original radiosonde sounding data to the scientific community as part of the YMC.

--- end ---